



2Fast™



Physical Properties

	<u>2Fast</u>
Color:	Amethyst/Peridot
Coverstock:	R2S™ Pearl Reactive
Weight Block:	N.O.S.™
Ball Finish:	1500-grit Polished
Logos:	2Fast, CG, Storm, Oval Bolt
Durometer:	74-76
Flare Potential:	4" - 5" (Medium-High)
Fragrance:	Grape
Available Weights:	10-16 lbs.

Ball Weight	Radius of Gyration	Differential
16 lbs.	2.53	.044
15 lbs.	2.53	.045
14 lbs.	2.59	.043
13 lbs.	2.68	.018
12 lbs.	2.70	.021



Resurfacing Method:

Follow the steps below to take the ball back to "out of the box" condition. Items needed: 500-grit Abralon, a Grey Scotch-Brite™ Pad, Storm® Step Two™ Polish, a ball spinner and water. All sanding should be done on four sides of the ball. Side one - center of grip up, flip the ball 180 degrees for side two, turn 90 degrees for side three, and flip another 180 degrees for side four.

1. Using the 500-grit Abralon pad, sand the ball for 15 seconds on each side.
2. Using the Grey Scotch-Brite pad, sand the ball for 40 seconds on each side.
3. Using the Storm Step Two, polish the ball on two sides for 15 seconds on each side.

R2S™
COVERSTOCK



Suggested Maintenance:

Storm suggests using Reacta Shine™ Reactive Ball Cleaner/Polish to clean your bowling ball after every bowling session.

To touch up the surface, skip step #1 and use step #2 and #3 only. Storm suggests using step #2 and #3 from above, every 20-30 games. Use all steps every 50-60 games. This will increase longevity and create a more consistent reaction for your new Storm bowling ball.