

Groove™ Urethane Blue Sanded

Specifications

Covertstock

Conventional Urethane

Color: Blue

Hardness: 79-81

Factory Finish

320-grit

Core Dynamics

RG Max: 2.703"

RG Min: 2.684"

RG Diff: 0.019"

RG Avg: 8.3

Performance

Hook Potential: 50

Length: 210

Breakpoint Shape: 40

Available Weights

10-16 Pounds



Reaction Characteristics

Ready to start hooking the ball? Move up from Plastic to Urethane coverstock technology. Compared to Plastic, Urethane coverstock technology increases traction and hooking action in the oil, and Urethane coverstocks can be sanded or shined to create large differences in hook potential.

The **Groove Urethane Blue Sanded** outperforms and under prices the competition and is recommended for medium to drier lane conditions.

Plastic slips. The Groove grips. And grip is exactly what you need to improve your game. When you're ready to step up from plastic, get in the Groove.

Notes on Drilling

Note: The top dead center of the puddle weight block is marked by a pin visible on the surface of the ball. Groove 12-16 pound balls can be drilled using the techniques developed for two-piece balls that are detailed on the next page. Groove balls with large pin-outs will be rare so plan on using the layouts that require smaller pin-outs. Groove 10-11 pound balls should be drilled using standard label shifting techniques.

For the most up to date Product Line Information go to www.brunswickbowling.com