

Information Sheet

Brunswick 

Groove™ Urethane Dark Blue / Light Blue Polished

Specifications

Part Number

60-104775-93X

Covertstock

Conventional Urethane

Color: Dark Blue / Light Blue

Hardness: 79-81

Factory Finish

High Gloss Polish

Core Dynamics

RG Max: 2.703"

RG Min: 2.684"

RG Diff: 0.019"

RG Avg: 8.3

Performance

Hook Potential: 55


Length: 170

Breakpoint Shape: 55

Available Weights

10-16 Pounds

(10-11 use a spherical offset core)



GROOVE
URETHANE

Reaction Characteristics

Ready to start hooking the ball? Move up from Plastic to Urethane coverstock technology. Compared to Plastic, Urethane coverstock technology increases traction and hooking action in the oil, and Urethane coverstocks can be sanded or shined to create large differences in hook potential.

The **Groove Urethane Dark Blue / Light Blue Polished** outperforms and under prices the competition and is recommended for medium to drier lane conditions.

Plastic slips. The Groove grips. And grip is exactly what you need to improve your game. When you're ready to step up from plastic, get in the Groove.

Notes on Drilling

Note: The top dead center of the bullet weight block is marked by a pin visible on the surface of the ball. Groove 10-16 pound balls can be drilled using the techniques developed for two-piece balls that are detailed on the next page. Groove balls with large pin-outs will be rare so plan on using the layouts that require smaller pin-outs.

For the most up to date Product Line Information go to www.brunswickbowling.com