

C·(SYSTEM)™ ULTI-MAX

CFT ULTI-MAX PEARL COVERSTOCK

CFT **ulti-max pearl** is our newest breakthrough in Chemical Friction Technology. The CFT **ulti-max pearl** coverstock uses the highest concentration of the friction additive in order to maximize the chemical system. The key to CFT is creating more traction with chemical friction instead of mechanical friction. By using less mechanical friction to produce hook, the CFT **ulti-max pearl** coverstock provides enhanced projection down the lane while saving axis rotation for more energy on the backend and through the pins.

CORE

The new **Dual Flip I - Block** core incorporates a top and bottom flip block over a centered mass. The centered mass creates stability while the dual flip blocks keep the core revving to the backend all the way through the pins for improved pin action.

BALL MOTION

With its Rough Buff Finish, the **C·(System) ulti-max** skids effortlessly through the front, saving axis rotation in the mid-lane to grab the backend for strong continuous response to friction that cuts easily through the pins on medium to medium-oily lane conditions.

REACTION SETUP

The **C·(System) ulti-max** can be drilled using the standard drilling techniques developed for asymmetric bowling balls.

LIGHTWEIGHT ENGINEERING

At Brunswick, the unique core shape of each individual ball is used for weights from 14 to 16 pounds. This approach to lightweight ball engineering provides bowlers with consistent ball reaction characteristics across this weight range. At 12 and 13 pounds, Brunswick uses a generic core shape with a RG-differential that is close enough to the 14 to 16 pound shape so the same drilling instructions can be used.



16 LB

15 LB

14 LB

13 LB

12 LB

RG-MAX	2.570	2.585	2.604	2.632	2.655
RG-INT	2.553	2.568	2.587	2.621	2.644
RG-MIN	2.520	2.535	2.554	2.589	2.612
RG-DIFF	0.050	0.050	0.050	0.043	0.043
RG-ASY	0.017	0.017	0.017	0.011	0.011

PP[®]
Pro performance



SPECIFICATIONS

Hook Potential	Low(10)	155	High(185)
Length	Early(25)	110	Long(235)
Breakpoint Shape	Smooth Arc(10)	95	Angular(100)
RG Differential	Low(0)	.050	High(.060)
RG Average	Center Heavy(1)	4.4	Cover Heavy(10)

- Dual Flip I-Block Core
- CFT Ulti-Max Pearl Coverstock
- 3-Color, Black/Red/Silver Pearl
- Hardness: 75-76
- 500 & 1,500 Siaair Micro Pad; Rough Buff Finish
- Chart Position: Q-2
- Part No. 60-105383-93X

C·(System)
ulti-max

Brunswick[®]
BowlwithBrunswick.com

MAINTAINING YOUR BALL REACTION

Brunswick recommends the following procedures to maintain and restore the reaction characteristics of your Brunswick bowling balls:

1. Clean your Brunswick ball with **Brunswick Remove All** or similar ball cleaner after every use to reduce oil absorption.
2. If you think your Brunswick ball has lost some of its "out of the box" reaction, restore the ball to its original factory finish listed on the product information sheet. This is especially important for balls that are highly sanded or polished. Sand to 400-grit then use **Factory Finish High Gloss Polish by Brunswick** to restore the original factory finish on high gloss polish balls. Sand to 220-grit then use **Factory Finish Rough Buff by Brunswick** to restore the original factory finish on rough buff balls. For dull balls, wet sand with the Micro Pad grit listed on the product information sheet.
3. If there is a visible track on your ball, have your pro shop use a Haus or similar resurfacing machine to remove the track then restore the ball to its original factory finish. This service is available, for a fee, at many pro shops.
4. If your ball has more than 50 games on it, you may be able to increase mid-lane and back-end hooking action by removing oil from the coverstock. Remove the oil from the ball by gently warming it with either the **Revivor** or **Rejuvenator** pro shop devices that have been designed for this purpose. The service is available, for a fee, at many pro shops. Brunswick testing has shown that by combining the restoration of the factory finish, resurfacing of the track and oil removal, your Brunswick ball can maintain its original "out of the box" reaction for hundreds of games. **Do not use a home oven to remove oil. Temperatures cannot be adequately controlled and the ball may crack.**

5. Absorbent materials sold by other bowling ball manufacturers to remove oil can also be used on Brunswick bowling balls. Information to date seems to indicate that absorbent materials have a more limited ability to remove oil than warming. You may be disappointed with results on heavily oil soaked balls.

NOTE: Oil soaked balls tend to traction less in the oil and respond less to the dry boards on the lane. If you are matching-up using an oil soaked ball on wet/dry or broken down lane conditions, removing the oil from the ball will significantly change your match-up and possibly create undesirable over reactions.

For the most up-to-date product line information visit bowlwithbrunswick.com/balls.