

TECHNICAL INFORMATION

TECHNOLOGY: Flip block with core body.

BENEFITS:

FEATURES:

Creates dynamic ball properties generating track flare to increase

friction with the lane.

COVERSTOCK: Flexathane[™] by BASF

Flexathane produces a smooth,

controllable ball reaction.

HARDNESS:

75-78

ABC/WIBC Approved.

TECHNICAL SPECIFICATIONS:

DYNAMIC PROPERTIES

	Weight	Rg	Diff. Rg
	16 lb.	2.525	0.047
Ž	15 lb.	2.599	0.039
	14 lb.	2.621	0.041

TRACK FLARE:

4" to 6"

HOOK RATING

	Hook Rating TEC Rating**			
	(boards of hook*)	7000000		
MESSENGER™ BLACK	12	10	26	
MESSENGER™ Nautical blue	15	6	32	
MESSENGER™ CHERRY PEARL	14	5	32	

* For average speed and rotation

All balls were tested with out of box finish. **TEC rating is the percent decrease in kinetic energy. The TEC rating is an indication of the energy transferred from kinetic (forward velocity) to rotational (hook). The higher the TEC rating, the more hook up to that area of the lane.

ORDER INFORMATION:

AVAILABLE WEIGHTS:

10 - 16 lbs.

V59-02

ITEM NUMBER:

Black with Neon Green engraving

FACTORY FINISH:


600 Grit Sheen Finish





Columbia bowls the world over.®

For more information, visit your local pro shop. www.columbia300.com



Messenger Black

Messenger Cherry Pearl