Brunswick B

FURY Pearl Tour Edition

(Orange Pin)







Low High 90 **Hook Potential:** (10)Early Long Length: 125 (25)(235)**Breakpoint** Smooth Arc Angular 70 (10)(100)Shape High Low 0.044 Flare Potential: (0.060) (0.0)RG-average: Center Heavy Cover Heavy 2.8 (10)

Part Number

60-104877-93X

Coverstock

Rough Buff

High Octane Dry 3-color Pearl Blue / Red / Silver Hardness: 76-77 Factory Finish

Core Dynamics @ 16#

Two-component

Dynamically Symmetrical Core

RG-max: 2.515 RG-min: 2.471 RG-diff: 0.044 Average RG: 2.8

Shape: 70 Chart Position: J12

Available Weights 14-16 Pounds

Hook Potential: 90

Typical Breakpoint

Performance

Lenath: 125

Coverstock

Building on the success of the original Fury Pearl, the *Fury Pearl Tour Edition* utilizes a dry lane version of High Octane coverstock to create a ball reaction with increased length and a smoother back-end reaction.

Core

The Fury Pearl uses the original Fury's Torsion Symmetric core system. Known for its easy revving characteristics, the Torsion Core helps the Fury Pearl Tour Edition to create great midlane recovery for a dry lane ball.

Reaction Characteristics

Out of the Box: With its Rough Buff finish, the *Fury Pearl Tour Edition* will provide more length and a smoother back-end than the original Fury Pearl, making it a good match for medium to dry lane conditions.

If your Fury Pearl Tour Edition goes too long: Rough up the surface with 1000-grit or progressively rougher abrasives. If you Fury Pearl still goes too long you will need to use a ball with a more aggressive coverstock, such as the original Fury Pearl..

If your Fury Pearl hooks too early: You will need to use a less aggressive ball such as the Power Groove Dry.

To bring your *Fury Pearl Tour Edition* back to its original factory finish, sand the surface with 400-grit sand paper and use polish with Brunswick Factory Finish Rough Buff..

For the most up to date Product Line Information go to www.brunswickbowling.com

Brunswick B

FURY Pearl Tour Edition

(Orange Pin)

Maintaining Your Ball Reaction

Brunswick recommends the following procedures to maintain and restore the reaction characteristic of your Brunswick bowling balls:

- --Clean your Brunswick ball with Brunswick Remove All or similar ball cleaner after every use to reduce oil absorption.
- --If you think your Brunswick ball has lost some of its "Out of the Box" reaction, restore the ball to its original factory finish listed on the product information sheet. This is especially important for balls that are highly sanded or polished. Sand to 400-grit then use *Brunswick's Factory Finish High Gloss Polish* to restore the original factory finish on high gloss polish balls. Sand to 220-grit then use *Brunswick's Factory Finish Rough Buff* to restore the original factory finish on rough buff balls. For dull balls, wet sand with the sandpaper listed on the product information sheet.
- --If there is a visible track on your ball have your Pro Shop use a Haas or similar resurfacing machine to remove the track then restore the ball to its original factory finish. This service is available, for a fee, at many Pro Shops.
- --If your ball has more than 50 games on it, you may be able to increase mid-lane and back-end hooking action by removing oil from the coverstock. Remove the oil from the ball by gently warming it with either the *Revivor* or *Rejuvenator* Pro Shop devices that have been designed for this purpose. The service is available, for a fee, at many Pro Shops. Brunswick testing has shown that by combining the restoration of the factory finish, resurfacing of the track and oil removal, your Brunswick ball can maintain its original "Out of the Box" reaction for hundreds of games.
 Do not use a home oven to remove oil. Temperatures can not be adequately controlled, and the ball may crack.
- --Absorbent materials sold by other bowling ball manufactures to remove oil can also be used on Brunswick bowling balls. Information to date seems to indicate that absorbent materials have a more limited ability to remove oil than warming. You may be disappointed with results on heavily oil soaked balls.

Note: Oil soaked balls tend to traction less in the oil and respond less to the dry boards on the lane. If you are matching-up using an oil soaked ball on wet/dry or broken down lane conditions, removing the oil from the ball will significantly change your match-up and possibly create undesirable over reactions.

Ball Comparisons

Want to compare the performance of this ball to other Brunswick balls?

Go to our website at www.brunswickbowling.com. Click on *Balls*, then click on *Pro Shop Information*.

This page contains a link to the <u>Brunswick Ball Comparison Chart.</u> This chart allows you to see, at a glance, the performance of all Brunswick balls relative to each other, defined by their **Hook Potential** and **Arc Characteristics**. There's even an essay to help explain and guide you through the chart.

Lightweight Engineering

At Brunswick, the unique core shape of each individual ball is used for weights from 14 to 16 pounds. This approach to lightweight ball engineering provides bowlers with consistent ball reaction characteristics across this weight range. At 12 & 13 pounds, Brunswick uses a generic core shape with a RG-differential of 0.045. This differential is close enough to the 14-16 pound shape so that the same drilling instructions can be used.

Weight	16#	15#	14#	13#	12#	11#	10#
Core Shape				Not Available	Not Available	Not Available	Not Available
RG-max.	2.515	2.533	2.554				
RG-min.	2.471	2.490	2.511				
RG-diff.	0.044	0.043	0.043				