BALL NAMEDV8 Hell FPART NUMBER60-105391COLORBlack/RedCOREHell RaiseCOVERSTOCKClass 5 ReRG MAX2.591RG INT2.575RG MIN2.537		1-93X d/Yellow er Core		D V PRO			9
DIFFERENTIAL Asymmetric Diff Hook (1-185) Length (1-235) Breakpoint (1-100 Factory Finish	0.054 0.016 165 110		\sim back of ball \sim	DOU	3E 9	0ME ¥	ÛELL
RG MAX Rg INT Rg Min Rg Diff Rg Asy	<i>16LB</i> 2.580 2.564 2.526 0.054 0.016	<i>15LB</i> 2.591 2.575 2.537 0.054 0.016		<i>14LB</i> 2.607 2.591 2.553 0.054 0.016	131 2.6 2.6 2.5 0.0 0.0	532 521 589 943	<i>12LB</i> 2.655 2.644 2.612 0.043 0.011

BALL MOTION

Finished with a Rough Buff Polish, the Hell Raiser skids easily through the front and mid-lane with a very quick response to friction on the backend creating a highly angular motion that rips through the pins on medium oily to oily lane conditions.

REACTION SETUP

The DV8 Hell Raiser can be drilled using the standard drilling techniques developed for bowling balls with asymmetric cores.



ELL RAISER SPECS

14

BLACKLIGHT