



































BOWLING'S FIRST COLOR CODED REACTION SYSTEM



PIN BREAKER INC.

TOTALLY REACTIVE: URETHANE AT IT'S BEST!

BALL REACTION SELECTION GUIDE

		AESTHETIC PROFILE		
SYMMETRICAL	SYMMETRICAL	SURFACE TEXTURE 360 GRIT (CAN BE POLISHED TO DESIRED FINISH.)	ASYMMETRICAL	ASYMMETRICAL
		DESIGN TYPE		
Reactive Cover Stock High Density Symmetrical Inner Core Large Multi-Density Core	Reactive Cover Stock High Density Symmetrical Inner Core Dense Sub-Core Ceramic Filled	CORE ARCHITECTURE	Reactive Cover Stock High Density Asymmetrical Inner Core Dense Sub-Core Ceramic Filled	Reactive Cover Stock High Density Asymmetrical Inner Core Dense Sub-Core Ceramic Filled Internally Modified Higher Density Model
10 - 16 LBS.	13 - 16 LBS.	WEIGHTS AVAILABLE	13 - 16 LBS.	13 - 16 LBS.
LIGHT PURPLE	LIGHT PURPLE	COVER STOCK COLOR	LIGHT PURPLE	LIGHT PURPLE
YELLOW	WHITE	ENGRAVING COLOR	GREEN	ORANGE
		DIFFERENTIAL RADIUS OF GYRATION		
		FLARE POTENTIAL		
		HOOK POTENTIAL		
		COEFFICIENT OF FRICTION		
		COEFFICIENT OF RESTITUTION		
		DRILLING VERSATILITY		
5 10 15	5 10 15	NUMERICAL GAUGE	5 10 15	5 10 15
DRILL LIKE STANDARD 2 PC. BALLS		DRILLING TECHNIQUES	USE PIN BREAKER GUIDE A	

Balls depicted are covered by U.S. PAT #5,046,731 and other U.S. PAT. Pend.

300 S. CALHOUN STREET • FAIRBURY, IL 61739

815-692-4326 • 800-442-2903 • FAX: 815-692-2477



Pro Shops:

Call and Order Direct!