## Code Red™







**COVERSTOCK:** R2S<sup>™</sup> Hybrid Reactive

WEIGHT BLOCK: RAD⁴™ Core

FACTORY FINISH: 1500-grit Polished

BALL COLOR: 2-tone Red Pearl / Red Solid

**DUROMETER:** 73-75 Rex D-scale

**FLARE POTENTIAL:** 6" Plus (High)

FRAGRANCE: Cinnamon

**WEIGHTS:** 12-16 lbs.

SKU: TCR

Lbs.	RG	Diff.	Intermediate Diff.	Weight Block
16	2.49	0.056	0.022	
15	2.50	0.058	0.020	
14	2.55	0.056	0.014	
13	2.63	0.039	0.011	
12	2.72	0.022	0.006	

## Resurfacing to a 1500-grit Polished Factory Finish

Resurface to the original factory finish using a ball spinner.

- 1. 500-grit Abralon® Sand for 30 seconds on all four sides with firm pressure.
- 2. 1000-grit Abralon® Sand for 20 seconds on all four sides with light pressure.
- 3. 2000-grit Abralon® Sand for 20 seconds on all four sides with light pressure.
- 4. 4000-grit Abralon® Sand for 20 seconds on all four sides with light pressure.
- 5. Storm Step Two™ Polish lightly for 15 seconds each side.

Storm recommends using the suggested cleaner/polish daily. Storm also recommends touching up the surface with only the final step every 20 games and resurfacing completely every 30-50 games.





Use Reacta Shine™ Reactive Polish and Cleaner after every session.