



TROPICAL HEAT™

Physical Properties

Ball Weight	Radius of Gyration	Differential
16#	2.53	.040
15#	2.55	.038
14#	2.58	.035
13#	2.68	.018
12#	2.70	.021



Suggested Cleaner: Reacta Shine™ Reactive Ball Cleaner/Polish. Cleaning should be done after every bowling session.

Colors

Orange/Purple
Red/Blue
*Black/Silver

Fragrances

Creamsicle
Raspberry
Coco-rum Banana

Coverstock:

Reactor™ Pearl

Weight Block:

Turbine™ Core

Ball Finish:

1500-grit Polished

Logos:

Storm, CG, Oval Bolt, Heat

Durometer:

74-76


Flare Potential:

2"-3" (Medium-Low)

Resurface Method

Resurfacing: Follow the steps below to take the ball back to "out of the box" condition. Items needed: 500-grit Abralon®, a Grey Scotch-Brite™ Pad, Storm® Step Two™ Polish, a ball spinner and water. All sanding should be done on four sides of the ball. Side one - center of grip up, flip the ball 180 degrees for side two, turn 90 degrees for side three, and flip another 180 degrees for side four.

1. Using the 500-grit Abralon® pad, sand the ball for 15 seconds on each side.
2. Using the Grey Scotch-Brite™ pad, sand the ball for 40 seconds on each side.
3. Using the Storm Step #2, polish the ball on two sides for 15 seconds on each side.



Turbine™ Core

To touch up the surface, skip step #1 and use step #2 and #3 only. Storm suggests using step #2 and #3 from above, every 20-30 games. Use all steps every 60-80 games. This will keep the surface of the ball more consistent, resulting in greater longevity and a more consistent reaction of your new Storm bowling ball.

*Black/Silver features the Reactor™ Hybrid coverstock